

English



OM7800

Low-noise amplifier evaluation board with BGU7003 for 2.4 GHz ISM/WLAN

Demo board description

The BGU7003 LNA evaluation board simplifies the evaluation of the BGU7003 LNA for the 100 MHz FM application. The evaluation board enables testing of the device performance and requires no additional support circuitry. The board is fully assembled with the BGU7003, including the input and output matching circuitry as well as a decoupling capacitors to optimize the performance. The board is supplied with two SMA connectors for input and output connection to RF test equipment. The BGU7003 board is optimized for 2.8 V operation and consumes about 5 mA.

Features

- Two SMA connectors for input and output connection to RF test equipment
- \blacksquare Evaluation of the power on settling time t_{on} and the power off settling time t_{off}

Descriptive summary

Evaluation board content

BGU7003 LNA evaluation board in ESD safe packing

Applications

FM applications, like portable audio devices and mobile computing devices like feature phones, tablet PC's and notebook PC's.

All information on this product information page is subject to the subsequent disclaimers:

- General product disclaimer
- Quality and reliability disclaimer

Documentation for this product

Download all documentation (zip)

Filename	Туре	Format	Title	Date
UM10455	User manual	pdf	User manual for the BGU7003 100MHz LNA evaluation board (v.1.1)	2011-12-15

Demo boards

Type number	Ordering code(12NC)	Orderable part number	Products status	Region	Distributor	In stock	Order quantity	Inventory date	Buy online
OM7800/BGU7003/100	9340 660 69598		Volume production						

Products

Type number	Description	Status	Quick access			
BGU7003	Wideband silicon germanium low noise amplifier MMIC		Download datasheet			
			Order sample			

Support

If you have any questions related to this product please contact our support team via the support form: http://www.nxp.com/techsupport/